

Australian Lighting Solutions

LED Street light

Picture	Specification	Beam angle	CCT(K) (Bridgelux LED)	CCT(K) (CREE LED)	Dimension
	Power consumption: 50Watt	IP65			
	Power supply: MeanWell	LED chip: 56pcs 1w high power Bridgelux	2500k-3700k,3900 Lm	2500k-3700k,3900 Lm	
	Power efficiency: >85%	Lumens efficiency: 80-100Lm			
	Beam angle: 120°	Material: Aluminum+lens	3800-5000K, 4400 Lm	3800-5000K, 4400 Lm	
	Input voltage: AC100-240V		5000-7000k, 4900 Lm	5000-7000k, 4900 Lm	
DL-LLD-001					
	Power consumption: 60Watt	IP65			
	Power supply: MeanWell	LED chip: 56pcs 1w high power Bridgelux	2500k-3700k,4700 Lm	2500k-3700k,4700 Lm	
	Power efficiency: >85%	Lumens efficiency: 80-100Lm			
	Beam angle: 120°	Material: Aluminum+lens	3800-5000K, 5300 Lm	3800-5000K, 5300 Lm	
	Input voltage: AC100-240V		5000-7000k, 5900 Lm	5000-7000k, 5900 Lm	
DL-LLD-002					
	Power consumption: 80Watt	IP65			
	Power supply: MeanWell	LED chip: 56pcs 1w high power Bridgelux	2500k-3700k,6300 Lm	2500k-3700k,6300 Lm	
	Power efficiency: >85%	Lumens efficiency: 80-100Lm			
	Beam angle: 120°	Material: Aluminum+lens	3800-5000K, 7100 Lm	3800-5000K, 7100 Lm	
	Input voltage: AC100-240V		5000-7000k, 7900 Lm	5000-7000k, 7900 Lm	
DL-LLD-003					
	Power consumption: 100Watt	IP65			
	Power supply: MeanWell	LED chip: 112pcs 1w high power Bridgelux	2500k-3700k,7900 Lm	2500k-3700k,7900 Lm	
	Power efficiency: >85%	Lumens efficiency: 80-100Lm			
	Beam angle: 120°	Material: Aluminum+lens	3800-5000K, 7100 Lm	3800-5000K, 7100 Lm	
	Input voltage: AC100-240V		5000-7000k, 9900 Lm	5000-7000k, 9900 Lm	
DL-LLD-005					
	Power consumption: 120Watt	IP65			
	Power supply: MeanWell	LED chip: 112pcs 1w pcs high power Bridgelux	2500k-3700k,9600 Lm	2500k-3700k,9600 Lm	
	Power efficiency: >85%	Lumens efficiency: 80-95Lm			
	Beam angle: 120°	Material: Aluminum+armoured glass	3800-5000K, 10000 Lm	3800-5000K, 10000 Lm	
	Input voltage: AC100-240V		5000-7000k, 10800 Lm	5000-7000k, 10800 Lm	
DL-LLD-006					
	Power consumption: 150Watt	IP65			
	Power supply: MeanWell	LED chip: 224pcs 1w high power Bridgelux	2500k-3700k,11250 Lm	2500k-3700k,11250 Lm	
	Power efficiency: >85%	Lumens efficiency: 80-95Lm			
	Beam angle: 120°	Material: Aluminum+armoured glass	3800-5000K, 12750 Lm	3800-5000K, 12750 Lm	
	Input voltage: AC100-240V		5000-7000k, 14250 Lm	5000-7000k, 14250 Lm	
DL-LLD-007					
	Power consumption: 210Watt	IP65			
	Power supply: MeanWell	LED chip: 224pcs 1w high power Bridgelux	2500k-3700k,18000 Lm	2500k-3700k,18000 Lm	
	Power efficiency: >85%	Lumens efficiency: 80-95Lm			
	Beam angle: 120°	Material: Aluminum+armoured glass	3800-5000K, 19000 Lm	3800-5000K, 19000 Lm	
	Input voltage: AC100-240V		5000-7000k, 20000 Lm	5000-7000k, 20000 Lm	
DL-LLD-008					
	Power consumption: 240Watt	IP65			
	Power supply: MeanWell	LED chip: 120pcs 2w high power Bridgelux	2500k-3700k,20570 Lm	2500k-3700k,20570 Lm	
	Power efficiency: >85%	Lumens efficiency: 80-95Lm			
	Beam angle: 120°	Material: Aluminum+armoured glass	3800-5000K, 21710 Lm	3800-5000K, 21710 Lm	
	Input voltage: AC100-240V		5000-7000k, 22580 Lm	5000-7000k, 22580 Lm	
DL-LLD-009					
	Power consumption: 310Watt	IP65			
	Power supply: MeanWell	LED chip: 144pcs 2w high power Bridgelux	2500k-3700k,25710 Lm	2500k-3700k,25710 Lm	
	Power efficiency: >85%	Lumens efficiency: 80-95Lm			
	Beam angle: 120°	Material: Aluminum+armoured glass	3800-5000K, 27140 Lm	3800-5000K, 27140 Lm	
	Input voltage: AC100-240V		5000-7000k, 28570 Lm	5000-7000k, 28570 Lm	
DL-LLD-010					